



PRODUCT DATA SHEET



PRODUCT NAME/VISCOSITIES: TRX SYNTH 75w80 GL5

Product No	7765
Issue No.	2
Issue Date	29/08/13

DESCRIPTION:

A fully synthetic transmission oil to provide maximum protection and fuel economy.

APPLICATION:

For use where a 75w80 synthetic oil is required and specified by OEM's including BMW, Mercedes-Benz, Chrysler, Fiat, Nissan, PSA Group, Renault, VAG Group, Vauxhall / Opel, Alfa Romeo, Land Rover, Mini, Dodge, Ford and Volvo in manual gearboxes and axles where a high performance gear oil is required.

USER BENEFITS:

- Low friction and reduced drag providing increased performance and improved MPG.
- Improves the quality of the gear change.
- Resists the effects of high temperatures and heavy-duty use.
- The high level of mechanical protection allows extended service intervals to be used.

PERFORMANCE PROFILE:

- API GL-4 , GL-5

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	75w80
Specific Gravity @ 15°C	0.857
Kinematic Viscosity @ 100°C	8.7cSt
Kinematic Viscosity @ 40°C	46.0cSt
Viscosity Index	171
Brookfield Viscosity @ -40°C	133,000 cP
Pour Point °C	<-40
Flashpoint °C	>200

HEALTH AND SAFETY:

Health and Safety Data Sheet 7765 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

