



# PRODUCT DATA SHEET



## PRODUCT NAME/VISCOSITIES:

### CENTRAL HYDRAULIC FLUID

Product No	7631
Issue No.	2
Issue Date	13/10/2015

## DESCRIPTION:

Fully Synthetic multifunction hydraulic fluid developed for the modern automotive industry.

## APPLICATION:

Recommended for the following requirements; power steering, suspension level control, hydro pneumatic control, active stability control, shock absorbers, traction control, cabriolet electronic roof mechanism, central locking etc.

## USER BENEFITS:

- Modern technology fluid with outstanding performance
- Gives protection to highly loaded hydraulic pumps
- Cold climate operational noise reduction
- Excellent anti corrosion, anti-wear and anti-foam additives

## PERFORMANCE PROFILE:

- Long-life synthetic hydraulic fluid for modern vehicles
- Not to be used in Automatic Transmissions
- Suitable for the following vehicles: Audi (VAG), Bentley, BMW/Mini, Chrysler/ Dodge/ Jeep, Citroën, Fendt, Ford, General Motors, MAN, Mercedes Benz, Peugeot PSA S71 2710 (LDS), Porsche, Saab, Volvo, VW

## TYPICAL CHARACTERISTICS:

Specific Gravity @ 15°C	0.835
Kinematic Viscosity @ 100°C	7.0cSt
Kinematic Viscosity @ 40°C	20.0cSt
Viscosity Index	359
Pour Point °C	-48
Flashpoint °C	125

## HEALTH AND SAFETY:

Health and Safety Data Sheet 7631 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)

